



Deton Engineering – Risk Assessment

Deton Wide Mouth Coupler with Fixed L-Bar



Deton Engineering - Risk Assessment


Product:	Deton Wide Mouth Coupler with Fixed L-Bar	Revision No.:	1	Page 2 of 14
Issue Date:	11 December 2013	Authorised:		

TABLE OF CONTENTS

1. Introduction to Deton Engineering
2. Details of Deton Engineering
3. Scope of Quality Management System (SABS ISO 9001:2008)
4. Risk Assessment Team
5. Excerpt from Mine Safety Act
6. Scope of Risk Assessment
7. Format of Risk Assessment
8. Procedure for Safe, Correct Use of Deton Wide Mouth Coupler with fixed L-Bar
9. Inspection and Maintenance of Deton Wide Mouth Coupler with fixed L-Bar by Customer
10. Repair of Deton Wide Mouth Coupler with fixed L-Bar
11. Risk Assessments -
 - 11.1 Effective Operation of Deton Wide Mouth Coupler with fixed L-Bar by Customer

Copyright ©

- This manual may not be copied or reproduced in any way without prior written permission.
- It is expected that the information contained herein remain confidential.
- Any enquiries concerning Deton Engineering's' Policies, Procedures or Products may be directed to Deton Engineering via our Representatives.





Deton Engineering - Risk Assessment

Product:	Deton Wide Mouth Coupler with Fixed L-Bar	Revision No.:	1	Page 3 of 14
Issue Date:	11 December 2013	Authorised:		

1. Introduction to the Deton Group of Companies

Deton Engineering (Pty) Ltd., was established in 1973 by Hercules du Preez, the first product being the Hercules Jack for mining applications.

From this date, Deton Engineering has specialised in the production of products with safety and efficiency in mind, especially for applications in the Mining and Industrial industries. The Deton Group is continuously focussed on the monitoring and improvement of production, reduced downtime, improved safety, and the servicing and support of our products which has made Deton a leader in its field.

Within the Deton Group of Companies are the following companies whose processes are incorporated in our Quality Management System –

Deton Engineering (Pty) Ltd. – Deton Engineering manufactures Jacks, Rail Benders, Snatch Blocks, Pulleys, Hercules Jack and related products for the Mining and Industrial markets.

Wearresist SA (Pty) Ltd. – Wearresist manufactures, sells and applies a range of wear-resistant coatings, based upon a resin matrix with a 90% alumina content, targeted at the Mining and Industrial markets.

Ceramic Linings (Pty) Ltd. – Ceramic Linings manufacture and market alumina ceramic tiles for high abrasion, high impact and high temperature applications. The products compliment the Wearresist products and can be used in conjunction in such environments.

Cutlass Products (Pty) Ltd. – Cutlass manufacture and market a range of corrosion and abrasion resistant products, aimed at the general Industrial market.

Densit S.A. (Pty) Ltd. – Densit supplies and applies a range of branded wear-resistant products to the general industrial markets, under license from Densit Norway.



Deton Engineering - Risk Assessment

Product:	Deton Wide Mouth Coupler with Fixed L-Bar	Revision No.:	1	Page 4 of 14
Issue Date:	11 December 2013	Authorised:		

2. Details of Deton Engineering

This Risk Assessment refers to our Alberton based Head Office and Workshops, the details of which are –

6 Barium Street
Alrode Ext. 7
Alberton

P.O. Box 123920
Alrode
1450

Telephone: (011) 908-1922
E-mail: info@deton.co.za

Facsimile: (011) 864-5386
Website: www.deton.co.za

3. Scope of Quality Management System (SABS ISO 9001:2008)

The manufacture and repair of Hercules Jacks, Snatch Blocks, explosive boxes, mining equipment, rail benders, pipe splitters, railway rolling stock and re-railing equipment for mining, agriculture, postal and transport industries, the manufacture of corrosion-coating resins and wear-resistant linings, including the Cutlass range of epoxy products.

4. Risk Assessment Team

As a result of Deton Engineering's commitment to our customers, this Risk Assessment was conducted in order to ensure that all potential health, safety and related hazards are identified, the risks evaluated and controls implemented to ensure that the products are safe and without risk to our customers, as far as is reasonably practicable.

This Risk Assessment was compiled by the following team -

HP du Preez	Chairman
A du Preez	Managing Director
W Germishuisen	Sales
K Stewart	Sales
J Downward	Production
S Barley	Quality



Deton Engineering - Risk Assessment

Product:	Deton Wide Mouth Coupler with Fixed L-Bar	Revision No.:	1	Page 5 of 14
Issue Date:	11 December 2013	Authorised:		

5. Excerpt from Mine Safety Act (Act 29 of 1996)

Section 21 of the Mine Safety Act states the following -

21.(1) Any person who -


- (a) designs, manufactures, repairs, imports or supplies any article for use at a mine must ensure, as far as reasonably practicable -
 - (i) that the article is safe and without risk to health and safety when used properly and
 - (ii) that it complies with all requirements in terms of this Act;

21.(2) Any person who bears a duty in terms of sub-section (1) is relieved of that duty to the extent that is reasonable in the circumstances, if -

- (a) that person designs, manufactures, repairs, imports or supplies an article for or to another person; and
- (b) that person provides a written undertaking to take specified steps sufficient to ensure, as far as reasonably practicable, that the article will be safe and without risk to health and safety when used properly and that it complies with all prescribed requirements



Deton Engineering - Risk Assessment

Product:	Deton Wide Mouth Coupler with Fixed L-Bar	Revision No.:	1	Page 6 of 14
Issue Date:	11 December 2013	Authorised:		

6. Scope of Risk Assessment

The scope of this Risk Assessment is limited to the Deton Engineering Deton Wide Mouth Couplers with fixed L-bar and their application in a mining environment.

The objective of this Risk Assessment is to, as far as is reasonably practicable -

- identify all potential health, safety and related risks that the Deton Wide Mouth Coupler with fixed L-Bar could pose to the end-user
- measure the level of risk of the identified risks
- to recommend controls to alleviate or minimise the risks

The aim of this Risk Assessment is to provide end-users with detailed information that will permit them to use the Deton Wide Mouth Coupler with fixed L-Bar in a manner that is safe and provide optimal utilisation.





Deton Engineering - Risk Assessment

Product:	Deton Wide Mouth Coupler with Fixed L-Bar	Revision No.:	1	Page 7 of 14
Issue Date:	11 December 2013	Authorised:		

7. Format of Risk Assessment

The Risk Assessments are reflected in tabular format, with the specific aspects listed under the following main headings -

Potential Hazard - what could go wrong?

Consequences & Impact - what could happen if the instance occurred?

Recommendations & Controls - what measures are in place or should be taken?

The aspects are then rated in terms of -

Likelihood (What are the chances of the incident occurring, probability?)

LIKELIHOOD	Index Value	Result
Most likely	5	<input type="text"/>
Highly likely	4	
Likely	3	
Unlikely	2	
Highly unlikely	1	

Risk (What level of risk/element of danger would this incident expose you to?)

RISK	Index Value	Result
Very high risk	5	<input type="text"/>
High risk	4	
Medium risk	3	
Low risk	2	
Very low risk	1	

Severity (What could the severity of this incident be in terms of injuries, damage)?

SEVERITY	Index Value	Result
Extremely severe	5	<input type="text"/>
Quite severe	4	
Severe	3	
Not too severe	2	
Negligible	1	

From the above results, the "Risk Result" is tabulated as follows -

$$\text{RISK RESULT} = \text{LIKELIHOOD} \times \text{RISK} \times \text{SEVERITY}$$



Deton Engineering - Risk Assessment

Product:	Deton Wide Mouth Coupler with Fixed L-Bar	Revision No.:	1	Page 8 of 14
Issue Date:	11 December 2013	Authorised:		

7. Format of Risk Assessment (cont.)

The figure obtained (the Risk Result) is then classified as follows -

- 61 + High risk requiring immediate corrective action
- 39 - 60 High risk requiring corrective action (identified in RED)
- 21 - 40 Substantial risk with corrective action needed
- 6 - 20 Possible risk, must be brought to people's attention
- 5 Risk tolerable

This is reflected as "RR" on the accompanying Risk Assessment Charts.

8. Procedure for the Safe, Correct Use of the Deton Wide Mouth Coupler with fixed L-Bars

8.1 Coupling

Step	Action	Photograph
1	Check hopper is secured – sprag wheel	
2	Check coupling link has been inserted and is secure	
3	Operator to check that Driver is visible, and can see any signals given by Operator	
3	DO NOT LIFT LINK WITH HANDS – MAKE USE OF HANDLE PROVIDED	
4	Signal Driver to couple	

8.2 Uncoupling

Step	Action	Photograph
1	Secure hopper that is to be uncoupled by spragging wheel	
2	Operator to check that Driver is visible, and can see any signals given by Operator	
3	Turn L-key and lock in position using opposite coupler's pin to unlatch link	
4	Repeat step 4 on other coupler	
5	Signal Driver to uncouple	



Deton Engineering - Risk Assessment

Product:	Deton Wide Mouth Coupler with Fixed L-Bar	Revision No.:	1	Page 9 of 14
Issue Date:	11 December 2013	Authorised:		

9. Inspection & Maintenance of Deton Wide Mouth Coupler with fixed L-Bars by Customer

Due to the working environment, the load factors placed upon the products and the safety critical nature of the product, Deton Engineering recommends that all Deton Wide Mouth Coupler with fixed L-Bars are subject to regular inspection, and have provided Inspection Lists and Specifications detailing the acceptable wear tolerances of components for this purpose.

Inspection should consist of weekly maintenance/inspection and pre-trip/pre-shift inspection by the Driver. The nature of the inspection, what needs to be checked and the frequency is detailed below –

9.1 Daily Inspection for Loco Operators

- (a) check coupling link at both ends for any sign of “mushrooming” – scrap if evident
- (b) check that the latch can operate freely and returns to the locked position
- (c) check opening (“mouth”) to ensure that no obstructions are present

9.2 Weekly Inspection by Maintenance Staff

- (a) wash inside of coupler thoroughly with high pressure water
- (b) uncouple hoppers, ensuring that they are properly spragged
- (c) check latch pin for visible wear (refer Deton Specifications)
- (d) check latch for visible wear (deformation on face, refer Deton Specifications)
- (e) check buffer head for deformation – buffer head must not be flattened across face (refer Deton Specifications)
- (f) check bolts and nuts securing buffer are secured (4 off 8,8 bolts & nuts)

In order to ensure that the product's integrity is maintained, Deton Engineering recommend that use is made of Deton Engineering approved components only and that all repairs are performed by Deton Engineering.



Deton Engineering - Risk Assessment

Product:	Deton Wide Mouth Coupler with Fixed L-Bar	Revision No.:	1	Page 10 of 14
Issue Date:	11 December 2013	Authorised:		

10. Repair of Deton Wide Mouth Coupler with fixed L-Bars

The Deton Wide Mouth Coupler with fixed L-Bar consists of the following components -

- (a) Latch Pin
- (b) Latch
- (c) 2 off Centralising Springs
- (d) 2 off Stainless Steel springs
- (e) R-clip
- (f) M10 Bolts & Nuts (4 off)
- (g) L-key

The repair/replacement of these components is addressed below -

(a) Latch Pin

- Remove R-clip
- Remove 2 off M16 x 50 bolts on L-key and remove L-key
- Pull Latch Pin out of body
- Remove bolt & nut
- Remove 2 springs and discard
- Remove Latch
- Line up the Latch Pin keyway and insert latch
- Replace 2 springs and secure with 2 off M10 bolts and Nyloc nuts
- Apply Loctite to nut to ensure that it is secure and tighten

(b) Latch

Follow same procedure as Latch Pin if Latch requires replacement


(c) Latch/Spring Assembly

Follow same procedure as Latch Pin if Centralising Springs requires replacement

- Remove bolts and nuts by grinding
- Replace with new Centralising Springs



Deton Engineering - Risk Assessment

Product:	Deton Wide Mouth Coupler with Fixed L-Bar	Revision No.:	1	Page 11 of 14
Issue Date:	11 December 2013	Authorised:		

(d) Stainless Steel Springs

- Cut bolt off and remove
- Replace 2 off stainless steel springs
- Secure with 2 off M10 bolts & Nyloc nuts
- Apply Loctite to nut and secure
- Springs must be replaced in all instances – exposure to heat degrades spring quality

(e) R-clip

- Replace R-clip if visibly worn
- Grind off R-clip
- Weld new R-Clip in position





Deton Engineering - Risk Assessment

Product:	Deton Wide Mouth Coupler with Fixed L-Bar	Revision No.:	1	Page 12 of 14
Issue Date:	11 December 2013	Authorised:		

11.1 Risk Assessment – Effective Operation of Deton Wide Mouth Coupler with fixed L-Bar by Customer

ITEM	POTENTIAL HAZARD	CONSEQUENCES & IMPACT	RATINGS				RECOMMENDATIONS and CONTROLS
			L	R	S	RR	
1	Operator is positioned incorrectly when coupling	<ul style="list-style-type: none"> Operator caught between couplers/mine cars 	1	4	4	16	<ul style="list-style-type: none"> Design of coupler allows Operator to stand clear during coupling, in sight of Driver yet able to observe coupling operation Ensure Operators are trained in the correct, safe use of the coupler
2	Centre-line height of couplers varies	<ul style="list-style-type: none"> Failure to couple Damage to coupling link Derailement 	2	2	3	12	<ul style="list-style-type: none"> Coupler heights must be standardised Standardisation must also extend to Hopper types, wheel & axle sets as well as the 2 step link from loco to first hopper Correct maintenance of suspension components Ensure hoppers are chocked during coupling or uncoupling operations Ensure Operators are trained in the correct, safe use of the coupler



Deton Engineering - Risk Assessment

Product:	Deton Wide Mouth Coupler with Fixed L-Bar	Revision No.:	1	Page 13 of 14
Issue Date:	11 December 2013	Authorised:		

ITEM	POTENTIAL HAZARD	CONSEQUENCES & IMPACT	RATINGS				RECOMMENDATIONS and CONTROLS
			L	R	S	RR	
3	Incorrect coupling link used	<ul style="list-style-type: none"> Failure to couple Damage to centralising rubbers Damage to coupler 	1	2	2	4	<ul style="list-style-type: none"> Ensure that the correct link is used and is present (Red link) Ensure that only Deton Engineering spares are retained, both on surface and underground Ensure hoppers are chocked during coupling and uncoupling operations Ensure Operators are trained in the correct, safe use of the coupler
4	Damaged Couplers	<ul style="list-style-type: none"> Failure to couple Progressive damage to coupler and link 	1	2	2	4	<ul style="list-style-type: none"> Conduct Weekly inspection of coupling link and coupler assembly Ensure correct maintenance and inspection procedures are followed Ensure hoppers are chocked during coupling or uncoupling operation Ensure Operators are trained in the correct, safe use of the coupler
5	Excessive speed during coupling operation	<ul style="list-style-type: none"> Damage to coupler and link Derailement 	2	2	3	12	<ul style="list-style-type: none"> Ensure correct signals are used by Operators Ensure locomotives and related systems are in working order Ensure Operators and Drivers are trained in the correct, safe use of the coupler Enforce Disciplinary Procedures for operating outside Mine Procedures



Deton Engineering - Risk Assessment

Product:	Deton Wide Mouth Coupler with Fixed L-Bar	Revision No.:	1	Page 14 of 14
Issue Date:	11 December 2013	Authorised:		

ITEM	POTENTIAL HAZARD	CONSEQUENCES & IMPACT	RATINGS				RECOMMENDATIONS and CONTROLS
			L	R	S	RR	
6	Excessive play between link and latch	<ul style="list-style-type: none"> Reduced safe working load 	1	1	1	1	<ul style="list-style-type: none"> Inspect wear on coupling link as per maintenance and inspection procedures Inspect wear on coupling latch as per maintenance and inspection procedures Ensure staff are trained in the correct, safe use, inspection and maintenance of the coupler Check L-key in place & secure
7	Coupling latch fails to locate correctly	<ul style="list-style-type: none"> Possible runaway hoppers 	1	2	3	6	<ul style="list-style-type: none"> Ensure couplings are inspected on weekly basis, with particular attention to latch springs and regular cleaning using high pressure water Driver to check coupling as part of pre-start Inspection List Check L-key in place & secure
8	Derailment or Tip Over of Loco & Hoppers	<ul style="list-style-type: none"> Damage to loco & hoppers Injury, loss of life 					<ul style="list-style-type: none"> Enforce Disciplinary Procedures to ensure correct control and operation of loco's Ensure staff are trained in the correct, safe operation of underground loco's Once secured (chocked), following removal of R-clip, followed by latch pin, loco and hoppers can safely be uncoupled